



TopLab® Vertical®

Unique identification code of the product-type		TopLab® Vertical®
Intended use or uses of the Construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer		Compact laminates for interior application in walls and ceilings Type CGS according to EN438 part 4
Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 (5)		TRESPA International B.V. Wetering 20 / NL – 6002 SM Weert
System or systems of AVCP (= assessment and verification of constancy of performance)		System 3
Name and identification number of the notified body		NB 1173 / WFRGENT N.V.
Declared performance		
Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	D-s2,d0	EN 438 – 7:2005
Fire Resistance	NPD	
Water vapour permeability	NPD	
Resistance to fixings	6 mm ≥ 2.000 N 8 mm ≥ 3.000 N ≥ 10 mm ≥ 4.000 N	
Direct airborne sound insulation	NPD	
Flexural tensile strength	≥ 120 MPa	
Flexural modulus of elasticity	≥ 9000 MPa	
Thermal resistance / conductivity	NPD	
Release of formaldehyde	E1	
Durability: Resistance to immersion in boiling water	Mass increase ≤ 1 % Thickness increase ≤ 1 % Appearance ≥ 4	
Durability: Density	≥ 1,35 g/cm ³	

The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Gilles Rabot (CEO)

Weert, The Netherlands, January 2023