

GEPAXTM 7000 SHEET

PRODUCT DATASHEET

DESCRIPTION

GEPAXTM 7000 sheet is an opaque polycarbonate sheet, specifically developed for a wide range of internal industrial applications previously dominated by metals and upgraded commodity plastics. GEPAX 7000 sheet combines extremely high impact performance with good stiffness over a wide temperature range (-30 to 110 $^{\circ}$ C). GEPAX 7000 sheet provides high impact performance, very good heat resistance and excellent formability.

TYPICAL PROPERTY VALUES ◆

PROPERTY	TEST METHOD	UNITS	VALUE
PHYSICAL			
Density	ISO 1183	g/cm³	1.20
Water absorption, 50% RH, 23 °C	ISO 62	%	0.15
Water absorption, saturation, 23°C	ISO 62	%	0.35
MECHANICAL			
Yield stress 50 mm/min	ISO 527	MPa	>60
Yield strain 50 mm/min	ISO 527	%	6
Nominal strain at break 50 mm/min	ISO 527	%	>100
Tensile modulus 1 mm/min	ISO 527	MPa	2300
Flexural strength 2 mm/min	ISO 178	MPa	90
Flexural modulus 2 mm/min	ISO 178	MPa	2300
IMPACT			
Charpy impact, notched 23°C, 3.0 mm	ISO 179/1eA	kJ/m²	75
Izod impact, unnotched 23°C, 3.0 mm	ISO 180/1U	kJ/m²	NB
Izod impact, notched 23°C, 3.0 mm	ISO 180/1A	kJ/m²	70
THERMAL			
Vicat softening temperature, rate B/120	ISO 306	°C	145
Temperature of deflection under load (type A), 1.8 MPa, flat	ISO 75	°C	127
Thermal conductivity	ISO 8302	W/m.°C	0.2
Coefficient of linear thermal expansion, 23-55°C	ISO 11359-2	1/°C	7x10 ⁻⁵
Ball pressure test 125 ±2°C	IEC 60695-10-2	-	Pass
ELECTRICAL			
Volume resistivity	IEC 60093	Ohm.cm	>10 ¹⁵
Dielectric strength, in oil, 3.2 mm	IEC 60243-1	kV/mm	18
FIRE RATINGS			
Glow Wire Flammability Index (GWFI)	IEC 60695-2-12	°C	Pass 850°C (3mm)

These property values have been derived from LEXAN™ resin data for the material used to produce this sheet product.
Trademark of SABIC.

PROCESSING

GEPAX[™] 7000 sheet is an excellent candidate for thermoforming. It offers high, deep draw ratios, equal wall thickness distribution, and it can be formed into complex shapes using standard thermoforming equipment. Sandwich type heating systems give the best results. GEPAX 7000 sheet has a forming temperature range of 180 - 220°C. When forming, a draft angle of at least 3° should be allowed, and post mold shrinkage of 0.5 - 0.9% taken into account.

CHEMICAL RESISTANCE

GEPAX 7000 sheet has sufficient resistance to most mineral oils, greases, aliphatic hydrocarbons and acids under low or moderate stress levels. In applications where the GEPAX 7000 sheet will come into contact with aggressive chemicals, specific (application related) testing is always advised. Effective painting systems can improve chemical resistance.

PRE-DRYING

It is important to ensure that GEPAX 7000 sheet is kept free of moisture prior to thermoforming. A hot air circulating oven set at 120°C is recommended. Pre-drying times vary from 4-24hours, depending on sheet thickness.

ASSEMBLING

Parts made from GEPAX 7000 sheet can be assembled with plastics, metals, rubber and other materials using many types of adhesive bonding, welding and mechanical fastening techniques. Further information and advice is available on request.

PAINTING

For either functional or decorative reasons it may be necessary to apply a finish to sheets or vacuum formed parts. GEPAX 7000 sheet is an excellent candidate for use with a wide variety of modern decoration techniques. A list of approved paint systems and suppliers is available upon request.

PRODUCT AVAILABILITY

Product code: GEPAX 7000 sheet

Standard size: 1250 x 2050mm, 2050 x 3000mm

Gauges: 1.0 - 8.0mm

Textures: Polished/Polished (0) Polished/Matt (5) Polished/Suede (6), Polished/Haircell (11N) Standard

Colors: Black 78927, Light Gray 78944, Off White 78943.

Non Standard Colors: Red 68278, Dark Blue 28291, Light Blue 28293, Gray 78964, Brown 58961, Yellow 48225, Green

38241, Dark Gray 78959, Beige 58921.

Other colors/sizes are available by special request.

CONTACT US:

Middle East and Africa

SABIC Global Headquarters PO Box 5101 Riyadh 11422

Saudi Arabia

T +966 (0) 1 225 8000 F +966 (0) 1 225 9000 E info@sabic.com

Email sfs.info@sabic-ip.com

Americas

Specialty Film & Sheet One Plastics Avenue Pittsfield, MA 01201 USA

F (888) 443 2033

Toll-free 1 800 323 3783 ext.3 T 1 413 448 7125

 $E\ sfscustomerservice @ sabic-ip.com$

Furona

Specialty Film & Sheet Plasticslaan 1 4612 PX Bergen op Zoom

T +31 (0)164 293678 F +31 (0)164 293272 E sfs.info@sabic-ip.com

The Netherlands

Asia Pacific

Specialty Film & Sheet 2550 Xiupu Road Pudong 201319 Shanghai

China

T +86 21 2037 8188 F +86 21 2037 8288 E sfs.info@sabic-ip.com

DISCLAIMER: THE MATERIALS, PRODUCTS AND SERVICES OF SAUDI BASIC INDUSTRIES CORPORATION (SABIC) OR ITS SUBSIDIARIES OR AFFILIATES ("SELLER") ARE SOLD SUBJECT TO SELLER'S STANDARD CONDITIONS OF SALE, WHICH ARE AVAILABLE UPON REQUEST. INFORMATION AND RECOMMENDATIONS CONTAINED IN THIS DOCUMENT ARE GIVEN IN GOOD FAITH. HOWEVER, SELLER MAKES NO EXPRESS OR IMPLIED REPRESENTATION, WARRANTY OR GUARANTEE (I) THAT ANY RESULTS DESCRIBED IN THIS DOCUMENT WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN OR APPLICATION INCORPORATING SELLER'S MATERIALS, PRODUCTS, SERVICES OR RECOMMENDATIONS. UNLESS OTHERWISE PROVIDED IN SELLER'S STANDARD CONDITIONS OF SALE, SELLER SHALL NOT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS, SERVICES OR RECOMMENDATIONS DESCRIBED IN THIS DOCUMENT. Each user is responsible for making its own determination as to the suitability of Seller's materials, products, services or recommendations for the user's particular use through appropriate end-use and other testing and analysis. Nothing in any document or oral statement shall be deemed to alter or waive any provision of Seller's Standard Conditions of Sale or this Disclaimer, unless it is specifically agreed to in a writing signed by Seller. Statements by Seller concerning a possible use of any material, product, service or design do not, are not intended to, and should not be construed to grant any license under any patent or other intellectual property right of Seller or as a recommendation for the use of any material, product, service or design in a manner that infringes any patent or other intellectual property right.

SABIC and brands marked with ™ are trademarks of SABIC or its subsidiaries or affiliates. © 2014 Saudi Basic Industries Corporation (SABIC). All Rights Reserved.



[†] Any brands, products or services of other companies referenced in this document are the trademarks service marks and/or trade names of their respective holders.